



**Neff - D1613N0GB stainless steel
Conventional hood, 60 cm wide
Conventional hood**

- Suitable for ducted extraction and recirculation
- Switch control operation
- 3 speeds
- 1 x 40 W lights
- Universal charcoal grease filter
- Glass visor
- Ducted extraction rate according to DIN/EN 61591: max. 190 m³/h
- Suitable for ducted or re-circulated extraction
- Extraction rate freeblowing max. 210 m³/h

Optional accessories:

- Z5110X3 : Active carbon filter
- Z5200X0 : Accessory

Characteristics

Product name/family :
 Color chimney :
 Typology : Built-under (classic)
 Approval certificates : CE, VDE
 Length electrical supply cord (m) : 130.0
 Required niche size for installation (HxWxD) : x
 x
 Height of the chimney (mm) :
 Height of product, without chimney (mm) :
 Dimensions of the product, with chimney (if exists) (mm) : 140 x 598 x 510
 Net weight (kg) : 8.00
 Type of control : mechanical
 Number of speed settings : 3-stage
 Maximum output air extraction (m³/h) : 190
 Boost position output recirculating (m³/h) :
 Maximum output recirculating air (m³/h) : 150
 Boost position air extraction (m³/h) :
 Number of lights (Stck) : 1
 Noise level (dB) :
 Diameter of air outlet (mm) : 120 / 100
 Grease filter material : Not washable synthetic

Consumption and connection features

Connection Rating (W) : 125
 Current (A) :
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : GB plug
 Installation typology : Under cabinet

Alternative colors available:

- D1613S0GB : Extractor hoods
- D1613W0GB : Extractor hoods
- D1613B0GB : Extractor hoods

Extractor hoods
 Neff - D1613N0GB

Predecessor:
 Successor:

EAN code: 4242004070719

sales programme:

Included accessories: