

Fast assembly concealed hinge with integrated Silent System

- ▶ Sensys 8645i
- ▶ Opening angle 110°, packaging unit 200 ea.



- ▶ Concealed hinge with clip on installation and integrated Silent System
- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 24 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated +/- 2 mm overlay adjustment
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Hinge arm material: steel, nickel plated
- ▶ Hinge cup material: steel, nickel plated

Sensys 8645i, opening angle 110°

Cup assembly	Drilling pattern	Mounting drilling ø x T mm	full overlay	half overlay	inset	PU
			Base B 12.5 mm	Base B 3 mm	Base B -4 mm	
For screwing on TH 52		-	9 071 205	9 071 206	9 071 207	200 ea.
For pressing in TH 53		ø 10 x 11	9 071 208	9 071 209	9 071 210	200 ea.
Fix fast assembly THS 55		ø 10 x 6	9 071 220	9 071 221	9 071 222	200 ea.
For screwing on TB 52		-	9 071 223	9 071 224	9 071 225	200 ea.
For pressing in TB 53		ø 8 x 11	9 071 226	9 071 227	9 071 228	200 ea.
Fix fast assembly TB 55		ø 8 x 6	9 071 238	9 071 239	9 071 240	200 ea.