





# Fast assembly concealed hinge without integrated Silent System

- ▶ Sensys 8657, zero protrusion hinge
- ▶ Opening angle 165°



- ▶ Concealed hinge with clip on installation without integrated Silent System
- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness of 15 – 32 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 11.6 mm
- ▶ Integrated +/- 2 mm overlay adjustment
- ▶ Integrated depth adjustment +3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Opening angle can be reduced by means of optional accessories
- ▶ Zero protrusion hinge
- ▶ Hinge arm material: steel, nickel plated
- ▶ Hinge cup material: steel, nickel plated

## Sensys 8657, opening angle 165°

Cup assembly	Drilling pattern	Mounting drilling ø x T mm	full overlay	half overlay	PU
					
For screwing on TH 52		-	9 099 600	9 099 610	1/50 ea.
For pressing in TH 53		ø 10 x 11	9 099 601	9 099 611	1/50 ea.
Fix fast assembly THS 55		ø 10 x 6	9 099 603	9 099 613	1/50 ea.
For screwing on TB 52		-	9 099 620	9 099 630	1/50 ea.
For pressing in TB 53		ø 8 x 11	9 099 621	9 099 631	1/50 ea.
Fix fast assembly TB 55		ø 8 x 6	9 099 623	9 099 633	1/50 ea.