





Fast assembly concealed hinge with integrated Silent System

- ▶ Sensys 8657i zero protrusion hinge
- ▶ Opening angle 165°



- ▶ Concealed hinge with clip on installation and integrated Silent System
- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness of 15 – 32 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 11.6 mm
- ▶ Integrated +/- 2 mm overlay adjustment
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Opening angle can be reduced by means of optional accessories
- ▶ Zero protrusion hinge
- ▶ Hinge arm material: steel, nickel plated
- ▶ Hinge cup material: steel, nickel plated

Sensys 8657i, opening angle 165°

Cup assembly	Drilling pattern	Mounting drilling ø x T mm	full overlay	half overlay	PU
					
For screwing on TH 52		-	9 099 540	9 099 550	1/50 ea.
For pressing in TH 53		ø 10 x 11	9 099 541	9 099 551	1/50 ea.
Flash fast assembly TH 54		ø 10 x 11	9 099 542	9 099 552	1/50 ea.
Fix fast assembly THS 55		ø 10 x 6	9 099 543	9 099 553	1/50 ea.
For screwing on TB 52		-	9 099 560	9 099 570	1/50 ea.
For pressing in TB 53		ø 8 x 11	9 099 561	9 099 571	1/50 ea.
Flash fast assembly TB 54			9 099 562	9 099 572	1/50 ea.
Fix fast assembly TB 55		ø 8 x 6	9 099 563	9 099 573	1/50 ea.